

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number
WO 2004/001467 A1

- (51) International Patent Classification⁷: **G02B 6/25**
- (21) International Application Number:
PCT/SE2003/000950
- (22) International Filing Date: 10 June 2003 (10.06.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0201946-1 25 June 2002 (25.06.2002) SE
- (71) Applicant (for all designated States except US): **NYFORS
TEKNOLOGI AB** [SE/SE]; Solkraftsvägen 12, S-135 70
Stockholm (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **BÖTTCHER, Uwe**
[SE/SE]; Heleneborgsgatan 10 A, S-117 32 Stockholm
(SE).
- (74) Agents: **OLSSON, Jan et al.**; Bjerkéns Patentbyrå KB,
Box 1274, S-801 37 Gävle (SE).
- (81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AN ARRANGEMENT AND A METHOD FOR CLAMPING THIN RODS



(57) Abstract: An arrangement for clamping thin rods of glass or quartz having a diameter below 1 mm in two mutually-spaced clamping locations for holding a said rod extended between the two clamping locations. The arrangement also comprises first clamping means arranged to clamp the rod in a first clamping location. The first clamping means has a first clamping member (22) with a clamp face (23) of substantially V-groove type for receiving the rod in the groove (24). The first clamping member is movably arranged with respect to a framework (45) of the apparatus for clamping a rod.

WO 2004/001467 A1